

## SAFETY DATA SHEET

Creation Date 28-April-2009

Revision Date 25-April-2019

Revision Number 7

### 1. Identification

<b>Product Name</b>	Acetone
<b>Cat No. :</b>	A9-4; A9-20; A9-200; A11-1; A11-4; A11-20; A11-200; A11S-4; A13-20; A13-200; A16F-1GAL; A16P-1GAL; A16P-4; A16S-4; A16S-20; A18-1; A18-4; A18-20; A18-20LC; A18-200; A18-200LC; A18-500; A18CU1300; A18FB-19; A18FB-50; A18FB-115; A18FB-200; A18P-4; A18POP-19; A18POPB-50; A18RB-19; A18RB-50; A18RB-115; A18RB-200; A18RS-28; A18RS-50; A18RS-115; A18RS-200; A18S-4; A18SK-4; A18SS-19; A18SS-28; A18SS-50; A18SS-115; A18SS-200; A19-1; A19-4; A19RS-115; A19RS-200; A40-4; A928-4; A929-1; A929-4; A929-4LC; A929RS-19; A929RS-50; A929RS-200; A929SK-4; A929SS-28; A929SS-50; A929SS-115; A929SS-200; A946-4; A946-4LC; A946FB-200; A946RB-19; A946RB-50; A946RB-115; A946RB-200; A949-1; A949-4; A949-4LC; A949CU-50; A949N-119; A949N-219; A949POP-19; A949RS-28; A949RS-50; A949RS-115; A949SK-1; A949SK-4; A949SS-19; A949SS-28; A949SS-50; A949SS-115; A949SS-200; BP2403-1; BP2403-4; BP2403-20; BP2404-1; BP2404-4; BP2404-SK1; BP2404-SK4; HC300-1GAL; S70091; 22050131; 22050295
<b>CAS-No</b>	67-64-1
<b>Synonyms</b>	2-Propanone; Dimethyl ketone; (Certified ACS, HPLC, OPTIMA, Histological, Spectranalyzed, NF/FCC/EP, Pesticide, Electronic, GC Resolv, SAFE-COTE)
<b>Recommended Use</b>	Laboratory chemicals.
<b>Uses advised against</b>	Food, drug, pesticide or biocidal product use

#### Details of the supplier of the safety data sheet

##### Company

**Importer/Distributor**  
Fisher Scientific  
112 Colonnade Road,  
Ottawa, ON K2E 7L6,  
Canada  
Tel: 1-800-234-7437

##### **Manufacturer**

Fisher Scientific  
One Reagent Lane  
Fair Lawn, NJ 07410  
Tel: (201) 796-7100

##### **Emergency Telephone Number**

CHEMTREC®, Inside the USA: 800-424-9300  
CHEMTREC®, Outside the USA: 001-703-527-3887

### 2. Hazard(s) identification

#### Classification

**WHMIS 2015 Classification**

Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

<b>Flammable liquids</b>	Category 2
<b>Serious Eye Damage/Eye Irritation</b>	Category 2
<b>Specific target organ toxicity (single exposure)</b>	Category 3
Target Organs - Central nervous system (CNS).	
<b>Specific target organ toxicity - (repeated exposure)</b>	Category 2
Target Organs - Kidney, Liver, spleen, Blood.	
<b>Health Hazards Not Otherwise Classified</b>	Category 1
Prolonged or repeated contact may dry skin and cause irritation or cracking	

**Label Elements****Signal Word**

Danger

**Hazard Statements**

Highly flammable liquid and vapor

Causes serious eye irritation

May cause drowsiness and dizziness

May cause damage to organs through prolonged or repeated exposure

Prolonged or repeated contact may dry skin and cause irritation or cracking

**Precautionary Statements****Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharges

Do not breathe dust/fumes/gas/mist/vapours/spray

Wash face, hands and any exposed skin thoroughly after handling

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

**Response**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

IF INHALED: Remove person to fresh air and keep comfortable for breathing

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Call a POISON CENTER/ doctor if you feel unwell

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

**Storage**

Store in a well-ventilated place. Keep container tightly closed

Store locked up

**Disposal**

Dispose of contents/container to an approved waste disposal plant

### 3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Acetone	67-64-1	>95

### 4. First-aid measures

<b>General Advice</b>	If symptoms persist, call a physician.
<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
<b>Inhalation</b>	Move to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
<b>Ingestion</b>	Clean mouth with water and drink afterwards plenty of water.
<b>Most important symptoms/effects</b>	None reasonably foreseeable. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: May cause pulmonary edema: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
<b>Notes to Physician</b>	Treat symptomatically

### 5. Fire-fighting measures

<b>Suitable Extinguishing Media</b>	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Cool closed containers exposed to fire with water spray.
<b>Unsuitable Extinguishing Media</b>	Water may be ineffective
<b>Flash Point</b>	-20 °C / -4 °F
<b>Method -</b>	Closed cup
<b>Autoignition Temperature</b>	465 °C / 869 °F
<b>Explosion Limits</b>	
<b>Upper</b>	12.8 vol %
<b>Lower</b>	2.5 vol %
<b>Oxidizing Properties</b>	Not oxidising
<b>Sensitivity to Mechanical Impact</b>	No information available
<b>Sensitivity to Static Discharge</b>	No information available

#### Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

#### Hazardous Combustion Products

Carbon monoxide (CO) Carbon dioxide (CO<sub>2</sub>) Formaldehyde Methanol

#### Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### NFPA

**Health**  
2

**Flammability**  
3

**Instability**  
0

**Physical hazards**  
N/A

**6. Accidental release measures**

**Personal Precautions** Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

**Environmental Precautions** Should not be released into the environment.

**Methods for Containment and Clean Up** Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

**7. Handling and storage**

**Handling** Do not get in eyes, on skin, or on clothing. Wear personal protective equipment. Ensure adequate ventilation. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

**Storage** Flammables area. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition.

**8. Exposure controls / personal protection**

**Exposure Guidelines**

Component	Alberta	British Columbia	Ontario TWAEV	Quebec	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	TWA: 500 ppm TWA: 1200 mg/m <sup>3</sup> STEL: 750 ppm STEL: 1800 mg/m <sup>3</sup>	TWA: 250 ppm STEL: 500 ppm	TWA: 500 ppm STEL: 750 ppm	TWA: 500 ppm TWA: 1190 mg/m <sup>3</sup> STEL: 1000 ppm STEL: 2380 mg/m <sup>3</sup>	TWA: 250 ppm STEL: 500 ppm	(Vacated) TWA: 750 ppm (Vacated) TWA: 1800 mg/m <sup>3</sup> (Vacated) STEL: 2400 mg/m <sup>3</sup> (Vacated) STEL: 1000 ppm TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup>	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>

**Legend**

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

**Engineering Measures**

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

**Personal protective equipment**

**Eye Protection**

Goggles

**Hand Protection**

Wear appropriate protective gloves and clothing to prevent skin exposure.

Glove material	Breakthrough time	Glove thickness	Glove comments
Butyl rubber	> 480 minutes	0.5 mm	As tested under EN374-3 Determination of Resistance to Permeation by Chemicals

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

#### Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

**Recommended Filter type:** low boiling organic solvent Type AX Brown conforming to EN371

When RPE is used a face piece Fit Test should be conducted

#### Environmental exposure controls

Do not allow material to contaminate ground water system.

#### Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use. Wash hands before breaks and at the end of workday.

## 9. Physical and chemical properties

Physical State	Liquid
Appearance	Colorless
Odor	sweet
Odor Threshold	19.8 ppm
pH	7
Melting Point/Range	-95 °C / -139 °F
Boiling Point/Range	56 °C / 132.8 °F
Flash Point	-20 °C / -4 °F
Method -	Closed cup
Evaporation Rate	5.6 (Butyl Acetate = 1.0)
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	12.8 vol %
Lower	2.5 vol %
Vapor Pressure	247 mbar @ 20 °C
Vapor Density	2.0
Specific Gravity	0.790
Solubility	Soluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	465 °C / 869 °F
Decomposition Temperature	> 4°C
Viscosity	0.32 mPa.s @ 20 °C
Molecular Formula	C3 H6 O
Molecular Weight	58.08
Refractive index	1.358 - 1.359

## 10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Heat, flames and sparks. Incompatible products. Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Strong oxidizing agents, Strong reducing agents, Strong bases, Peroxides, Halogenated

compounds, Alkali metals, Amines

**Hazardous Decomposition Products** Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Formaldehyde, Methanol

**Hazardous Polymerization** Hazardous polymerization does not occur.

**Hazardous Reactions** None under normal processing.

## 11. Toxicological information

### Acute Toxicity

#### Product Information Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Acetone	5800 mg/kg ( Rat )	> 15800 mg/kg (rabbit) > 7400 mg/kg (rat)	76 mg/l, 4 h, (rat)

**Toxicologically Synergistic Products** Carbon tetrachloride; Chloroform; Trichloroethylene; Bromodichloromethane; Dibromochloromethane; N-nitrosodimethylamine; 1,1,2-Trichloroethane; Styrene; Acetonitrile, 2,5-Hexanedione; Ethanol; 1,2-Dichlorobenzene

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Irritation** Irritating to eyes and skin

**Sensitization** No information available

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Acetone	67-64-1	Not listed	Not listed	Not listed	Not listed	Not listed

**Mutagenic Effects** No information available

**Reproductive Effects** No information available.

**Developmental Effects** No information available.

**Teratogenicity** No information available.

**STOT - single exposure** Central nervous system (CNS)

**STOT - repeated exposure** Kidney Liver spleen Blood

**Aspiration hazard** No information available

**Symptoms / effects, both acute and delayed** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: May cause pulmonary edema: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

**Endocrine Disruptor Information** No information available

**Other Adverse Effects** The toxicological properties have not been fully investigated.

## 12. Ecological information

### Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Acetone	NOEC = 430 mg/l (algae; 96 h)	Oncorhynchus mykiss: LC50 = 5540 mg/l 96h Alburnus alburnus: LC50 = 11000 mg/l 96h Leuciscus idus: LC50 =	EC50 = 14500 mg/L/15 min	EC50 = 8800 mg/L/48h EC50 = 12700 mg/L/48h EC50 = 12600 mg/L/48h

		11300 mg/L/48h Salmo gairdneri: LC50 = 6100 mg/L/24h		
--	--	--	--	--

**Persistence and Degradability** Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** No information available.

**Mobility** Will likely be mobile in the environment due to its volatility.

Component	log Pow
Acetone	-0.24

### 13. Disposal considerations

**Waste Disposal Methods** Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Acetone - 67-64-1	U002	-

### 14. Transport information

#### DOT

UN-No UN1090  
 Proper Shipping Name ACETONE  
 Hazard Class 3  
 Packing Group II

#### TDG

UN-No UN1090  
 Proper Shipping Name ACETONE  
 Hazard Class 3  
 Packing Group II

#### IATA

UN-No UN1090  
 Proper Shipping Name ACETONE  
 Hazard Class 3  
 Packing Group II

#### IMDG/IMO

UN-No UN1090  
 Proper Shipping Name ACETONE  
 Hazard Class 3  
 Packing Group II

### 15. Regulatory information

#### International Inventories

Component	DSL	NDSL	TSCA	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Acetone	X	-	X	200-662-2	-		X	X	X	X	KE-2936 7

#### Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Component	Canada - National Pollutant Release Inventory (NPRI)	Canadian Environmental Protection Agency (CEPA) - List of Toxic Substances	Canada's Chemicals Management Plan (CEPA)
Acetone	Part 4 Substance		

---

## 16. Other information

<b>Prepared By</b>	Regulatory Affairs Thermo Fisher Scientific Email: EMSDS.RA@thermofisher.com
<b>Creation Date</b>	28-April-2009
<b>Revision Date</b>	25-April-2019
<b>Print Date</b>	25-April-2019
<b>Revision Summary</b>	This document has been updated to comply with the requirements of WHMIS 2015 to align with the Globally Harmonised System (GHS) for the Classification and Labelling of Chemicals.

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**