

GEORGIA INSTITUTE OF TECHNOLOGY
SCHOOL of ELECTRICAL and COMPUTER ENGINEERING

EE 2025 Fall 2001
Lab #3: AM and FM Sinusoidal Signals

Date: 11–17 Sept 2001

This is *the official* Lab#3 description; it is nearly *identical* to Lab-A in Appendix C.4 of the text.

You should read the Pre-Lab section of the lab and do all the exercises in the Pre-Lab section before your assigned lab time. You **MUST** complete the online Pre-lab exercise on Web-CT at the beginning of your scheduled lab session. You can use MATLAB and also consult your lab report or any notes you might have, but you cannot discuss the exercises with any other students. You will have approximately 20 minutes at the beginning of your lab session to complete the online Pre-Post-Lab exercise. The Pre-Post-Lab exercise for this lab includes some questions about concepts from the previous Lab report as well as questions on the Pre-Lab section of this lab.

The Warm-up section of each lab must be completed **during your assigned Lab time** and the steps marked *Instructor Verification* must also be signed off **during the lab time**. One of the laboratory instructors must verify the appropriate steps by signing on the **Instructor Verification** line. When you have completed a step that requires verification, simply raise your hand and demonstrate the step to the TA or instructor. After completing the warm-up section, turn in the verification sheet to your TA.

It is only necessary to turn in Section 4 as this week's lab report. More information on the lab report format can be found on Web-CT under the "Information" link. You should **label** the axes of your plots and include a title and Figure number for every plot. Every plot should be referenced by Figure number in your text discussion. In order to make it easy to find all the plots, include each plot *inlined* within your report. For more information on how to include figures and plots from MATLAB to your report file, consult the "information" link on Web-CT. If you still do not know how to do so, ask your TA.

Forgeries and plagiarism are a violation of the honor code and will be referred to the Dean of Students for disciplinary action. You are allowed to discuss lab exercises with other students and you are allowed to consult old lab reports but the submitted work should be original and it should be your own work.

The lab report and verification will be graded out of 100 points. The Pre-Post-Lab questions will be graded separately and will be worth about 20–30 points per lab.

The report will be **due during the period 18-Sept to 24-Sept at the start of your lab.**

1 Introduction

The objective of this lab is to introduce more complicated signals that are related to the basic sinusoid. These signals which implement frequency modulation (FM) and amplitude modulation (AM) are widely used in communication systems such as radio and television, but they also can be used to create interesting sounds that mimic musical instruments. There are a number of demonstrations on the CD-ROM that provide examples of these signals for many different conditions.



CD-ROM

FM Syn-
thesis

2 Pre-Lab

We have spent a lot of time learning about the properties of sinusoidal waveforms of the form:

$$x(t) = A \cos(2\pi f_0 t + \phi) = \Re \left\{ A e^{j\phi} e^{j2\pi f_0 t} \right\} \quad (1)$$

In this lab, we will extend our treatment of sinusoidal waveforms to more complicated signals composed of sums of sinusoidal signals, or sinusoids with changing frequency.

2.1 Amplitude Modulation

If we add several sinusoids, each with a different frequency (f_k) we can express the result as:

$$x(t) = \sum_{k=1}^N A_k \cos(2\pi f_k t + \phi_k) = \Re \left\{ \sum_{k=1}^N (A_k e^{j\phi_k}) e^{j2\pi f_k t} \right\} \quad (2)$$

where $A_k e^{j\phi_k}$ is the complex amplitude of the k^{th} complex exponential term. The choice of f_k will determine the nature of the signal—for amplitude modulation or beat signals we pick two or three frequencies very close together, see Chapter 3.

2.2 Frequency Modulated Signals

We will also look at signals in which the frequency varies as a function of time. In the constant-frequency sinusoid (1) the argument of the cosine is also the exponent of the complex exponential, so the phase of this signal is the exponent ($2\pi f_0 t + \phi$). This phase function changes *linearly* versus time, and its time derivative is $2\pi f_0$ which equals the constant frequency of the cosine.

A generalization is available if we adopt the following notation for the class of signals with time-varying phase:

$$x(t) = A \cos(\psi(t)) = \Re \{ A e^{j\psi(t)} \} \quad (3)$$

The time derivative of the phase from (3) gives a frequency

$$\omega_i(t) = \frac{d}{dt} \psi(t) \quad (\text{rad/sec})$$

but we prefer units of hertz, so we divide by 2π to define the *instantaneous frequency*:

$$f_i(t) = \frac{1}{2\pi} \frac{d}{dt} \psi(t) \quad (\text{Hz}) \quad (4)$$

2.3 Chirp, or Linearly Swept Frequency


A *chirp* signal is a sinusoid whose frequency changes linearly from a starting value to an ending one. The formula for such a signal can be defined by creating a complex exponential signal with quadratic phase by defining $\psi(t)$ in (3) as

$$\psi(t) = 2\pi\mu t^2 + 2\pi f_0 t + \phi$$

The derivative of $\psi(t)$ yields an instantaneous frequency (4) that changes *linearly* versus time.

$$f_i(t) = 2\mu t + f_0$$

The slope of $f_i(t)$ is equal to 2μ and its intercept is equal to f_0 . If the signal starts at time $t = 0$ secs., then f_0 is also the starting frequency. The frequency variation produced by the time-varying phase is called *frequency modulation*, and this class of signals is called FM signals. Finally, since the linear variation of the frequency can produce an audible sound similar to a siren or a chirp, the linear-FM signals are also called “chirps.”



2.4 MATLAB Synthesis of Chirp Signals

The following MATLAB code will synthesize a chirp:

```
fsamp = 11025;
dt = 1/fsamp;
dur = 1.8;
tt = 0 : dt : dur;
psi = 2*pi*(100 + 200*tt + 500*tt.*tt);
xx = real( 7.7*exp(j*psi) );
soundsc( xx, fsamp );
```

- Determine the total duration of the synthesized signal in seconds, and also the length of the `tt` vector.
- In MATLAB signals can only be synthesized by evaluating the signal's defining formula at discrete instants of time. These are called *samples* of the signal. For the chirp we do the following:

$$x(t_n) = A \cos(2\pi\mu t_n^2 + 2\pi f_0 t_n + \phi)$$

In the MATLAB code above, what is the value for t_n ? What are the values of A , μ , f_0 , and ϕ ?

- Determine the range of frequencies (in hertz) that will be synthesized by the MATLAB script above. Make a sketch by hand of the instantaneous frequency versus time. What are the minimum and maximum frequencies that will be heard?
- Listen to the signal to determine whether the signal's frequency content is increasing or decreasing (use `soundsc()`). Notice that `soundsc()` needs to know the rate at which the signal samples were created. For more information do `help sound` and `help sound()`.

3 Warm-up

The instructor verification sheet may be found at the end of this lab. The “Beat Control GUI” is part of the *DSP First* toolbox, and it should be on the MATLAB path already in the VL-252 lab.

3.1 Beat Control GUI

To assist you in your experiments with beat notes and AM signals, the tool called `beatcon` has been created. This *user interface controller* will exhibit the basic signal shapes for beat signals and play the signals. A small control panel will appear on the screen with *buttons* and *sliders* that vary the different parameters for the beat signals. It can also call a user-written function called `beat.m`. Experiment with the `beatcon` control panel and use it to produce a beat signal with two frequency components at 850 Hz and 870 Hz. Demonstrate the plot and sound to your TA.



Instructor Verification (separate page)

3.2 Function for a Chirp

Use the code provided in the warm-up as a starting point in order to write a MATLAB function that will synthesize a “chirp” signal according to the following comments:

```

function [xx,tt] = mychirp( f1, f2, dur, fsamp )
%MYCHIRP      generate a linear-FM chirp signal
%
% usage:      xx = mychirp( f1, f2, dur, fsamp )
%
%      f1 = starting frequency
%      f2 = ending frequency
%      dur = total time duration
%      fsamp = sampling frequency (OPTIONAL: default is 11025)
%
%      xx = (vector of) samples of the chirp signal
%      tt = vector of time instants for t=0 to t=dur
%
if( nargin < 4 )    %-- Allow optional input argument
    fsamp = 11025;
end

```

As a test case, generate a chirp sound whose frequency starts at 2500 Hz and ends at 500 Hz; its duration should be 1.5 sec. Listen to the chirp using the `soundsc` function. Include a listing of the `mychirp.m` function that you wrote.

Instructor Verification (separate page)

3.3 Advanced Topic: Spectrograms

It is often useful to think of signals in terms of their spectra. A signal's spectrum is a representation of the frequencies present in the signal. For a constant frequency sinusoid as in (1) the spectrum consists of two spikes, one at $2\pi f_0$, the other at $-2\pi f_0$. For more complicated signals the spectra may be very interesting and, in the case of FM, the spectrum is considered to be time-varying. One way to represent the time-varying spectrum of a signal is the *spectrogram* (see Chapter 3 in the text). A spectrogram is found by estimating the frequency content in short sections of the signal. The magnitude of the spectrum over individual sections is plotted as intensity or color on a two-dimensional plot versus frequency and time.

When unsure about a command, use `help`.

There are a few important things to know about spectrograms:

1. In MATLAB the function `specgram` will compute the spectrogram, as already explained in a recent lecture. Type `help specgram` to learn more about this function and its arguments.
2. Spectrograms are numerically calculated and only provide an estimate of the time-varying frequency content of a signal. There are theoretical limits on how well they can actually represent the frequency content of a signal. Lab 11 (in the text) will treat this problem when we use the spectrogram to extract the frequencies of piano notes.
3. A common call to the function is `specgram(xx, 1024, fs)`. The second argument¹ is the *window length* which could be varied to get different looking spectrograms. The spectrogram is able to “see” the separate spectrum lines with a longer window length, e.g., 1024 or 2048.²

¹If the second argument is made equal to the “empty matrix” then its default value of 256 is used.

²Usually the window length is chosen to be a power of two, because a special algorithm called the FFT is used in the computation. The fastest FFT programs are those where the signal length is a power of 2.



4. If you are working at home, you might not have the `specgram()` function because it is part of the “Signal Processing Toolbox.” In that case, use the function `plotspec(xx, fs)` which can be downloaded from Web-CT (you also need to download `spectgr.m`).³

• Note: The argument list for `plotspec()` has a different order from `specgram`, because `plotspec()` uses an optional third argument for the *window length* (default value is 256). In addition, `plotspec()` does not use color for the spectrogram; instead, darker shades of gray indicate larger values with black being the largest.

In order to see what the spectrogram produces, run the following code:

```
fs=8000; xx = cos(3000*pi*(0:1/fs:0.5)); specgram(xx,1024,fs); colorbar
```

or, if you are using `plotspec(xx, fs)`:

```
fs=8000; xx = cos(3000*pi*(0:1/fs:0.5)); plotspec(xx,fs,1024); colorbar
```

Notice that the spectrogram image contains one horizontal line at the correct frequency of the sinusoid.

4 Lab: Chirps and Beats

For the lab exercise and lab report, you will synthesize some AM and FM signals. In order to verify that they have the correct frequency content, you will use the spectrogram. Your lab report should discuss the connection between the “time-domain” definition of the signal and its “frequency-domain” content.

4.1 Beat Notes

In the section on beat notes in Chapter 3 of the text, we analyzed the situation in which we had two sinusoidal signals of slightly different frequencies; i.e.,

$$x(t) = A \cos(2\pi(f_c - f_\Delta)t) + B \cos(2\pi(f_c + f_\Delta)t) \quad (5)$$

In this part, we will compute samples of such a signal and listen to the result.

- (a) Write an M-file called `beat.m` that implements (5) and has the following as its first lines:

```
function [xx, tt] = beat(A, B, fc, delf, fsamp, dur)
%BEAT compute samples of the sum of two cosine waves
% usage:
% [xx, tt] = beat(A, B, fc, delf, fsamp, dur)
%
% A = amplitude of lower frequency cosine
% B = amplitude of higher frequency cosine
% fc = center frequency
% delf = frequency difference
% fsamp = sampling rate
% dur = total time duration in seconds
% xx = output vector of samples
%--Second Output:
% tt = time vector corresponding to xx
```

³Actually, you should download the ZIP file with all the new/updated M-files for ECE-2025.

Include a copy of your M-file in your lab report. You might want to call the `syn_sin()` function written in Lab 2 to do the calculation. The function should also generate its own time vector, because that vector can be used to define the horizontal axis when plotting.

- (b) To assist you in your experiments with beat notes a tool called `beatcon` has been created. This *user interface controller* is able to call your function `beat.m`, if you check the box Use External beat() in the lower left-hand corner of the GUI. Therefore, before you invoke `beatcon` you should be sure your M-file is free of errors. Also, make sure that your `beat.m` function is on the MATLAB path.

Test the M-file written in part (a) via `beatcon` by using the values $A=10$, $B=10$, $f_c=1000$, $delf=10$, $f_{\text{samp}}=11025$, and $\text{dur}=1$ secs. Plot the first 0.2 seconds of the resulting signal. Describe the waveform and explain its properties. Hand in a copy of your plot with measurements of the period of the “envelope” and period of the high frequency signal underneath the envelope.

- (c) (Optional)⁴ Experiment with different values of the frequency difference f_{Δ} . Listen to the sounds (there is a *button* on `beatcon` that will do this for you automatically) and think about the relationship between the sound and waveform.

4.2 More on Spectrograms

Beat notes provide an interesting way to investigate the time-frequency characteristics of spectrograms. Although some of the mathematical details are beyond the reach of this course, it is not difficult to appreciate the following issue: there is a fundamental trade-off between knowing which frequencies are present in a signal (or its spectrum) and knowing how those frequencies vary with time. As mentioned previously in Section 3.3, a spectrogram estimates the frequency content over short sections of the signal. If we make the section length very short we can track rapid changes in the frequency. However, shorter sections lack the ability to do accurate frequency measurement because the amount of input data is limited. On the other hand, long sections can give excellent frequency measurements, but fail to track frequency changes well. For example, if a signal is the sum of two sinusoids whose frequencies are nearly the same, a long section length is needed to “resolve” the two sinusoidal components. This trade-off between the section length (in time) and frequency resolution is equivalent to Heisenberg’s Uncertainty Principle in physics. More discussion of the spectrogram will be undertaken in Chapter 9 and Lab 11, if you want to read ahead.

A beat note signal may be viewed as a single frequency signal whose amplitude varies with time, *or* as two signals with different constant frequencies. Both views will be useful in evaluating the effect of window length when finding the spectrogram of a beat signal.

- (a) Create and plot a beat signal with
- (i) $f_{\Delta} = 32$ Hz
 - (ii) $T_{\text{dur}} = 0.26$ sec
 - (iii) $f_s = 11025$ Hz
 - (iv) $f_c = 2000$ Hz
- (b) Find the spectrogram using a window length of 2048 using the commands:
- ```
specgram(x, 2048, fsamp); colormap(1-gray(256)).
```
- Comment on what you see. Are the correct frequencies present in the spectrogram? If necessary, use the zoom tool to examine the important region of the spectrogram.

---

<sup>4</sup>“Optional” means that you do not have to include this in your lab report.



- (c) Find the spectrogram using a window length of 16 using the commands:  
`specgram(x,16,fsamp); colormap(1-gray(256)).`  
Comment on what you see, and compare to the previous spectrogram.

### 4.3 Spectrogram of a Chirp

Use the `mychirp` function (written during the Warm-up) to synthesize a “chirp” signal for your lab report. Use the following parameters:

1. A total time duration of 3 secs. with a D/A conversion rate of  $f_s = 11025$  Hz.
2. The instantaneous frequency starts at 5,000 Hz and ends at 300 Hz.

Listen to the signal. What comments can you make regarding the sound of the chirp (e.g., is the frequency movement linear)? Does it chirp down, or chirp up?

Create a spectrogram of this chirp signal, and use it to verify that you have the correct instantaneous frequencies.

### 4.4 A Chirp Puzzle

Synthesize a second “chirp” signal (for your lab report) with the following parameters:

1. A total time duration of 3 secs. with a D/A conversion rate of  $f_s = 11025$  Hz.
2. The instantaneous frequency starts at 3,000 Hz and ends at  $-2,000$  Hz (negative frequency).

Listen to the signal. Does it chirp down, or chirp up, or both?

Create a spectrogram of this second chirp signal.

Use the theory of the spectrum (with its positive and negative frequency components) to help explain what you hear and what you see in the spectrogram. In other words, the changing instantaneous frequency implies that the frequency components in the spectrum are moving.

**Lab #3**

**ECE-2025**

**Fall-2001**

**INSTRUCTOR VERIFICATION SHEET**

Turn this page in to your TA before the end of your lab period.

Name: \_\_\_\_\_

Date of Lab: \_\_\_\_\_

Part 3.1 Demonstrate usage of the Beat Control GUI.

Verified: \_\_\_\_\_

Date/Time: \_\_\_\_\_

Part 3.2 Demonstrate the `mychirp.m` function. In the space below write how you would call the function with a correct set of arguments.

Verified: \_\_\_\_\_

Date/Time: \_\_\_\_\_