

Printing date 10/10/2014

Reviewed on 10/10/2014

### 1 Identification of the substance/mixture and of the company

- · Product identifier
- · Trade name: 950 PMMA Series Resists in Anisole
- · Product number:

M230001, M230002, M230003, M230004, M230504, M230005, M230505, M230006, M230007, M230008, M230009, M230010, M230011, M230012, M230013, M230015

- · Application of the substance / the mixture Photoresist
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MicroChem Corp.

200 Flanders Road

Westborough, MA 01581 USA

Information department:

Product Safety

Email: productsafety@microchem.com

Emergency telephone number:

MicroChem Corp: 617-965-5511

Chemtree USA Emergency: 800-424-9300

Chemtrec International Emergency: 703-527-3887

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

· Signal word Warning

· Hazard-determining components of labeling:

Anisole

· Hazard statements

H226 Flammable liquid and vapor.

H332 Harmful if inhaled.

H315 Causes skin irritation.

(Contd. on page 2)



Printing date 10/10/2014

100-66-3 Anisole

· Additional Components:

STOT SE 3, H335

9011-14-7 Poly(methyl methacrylate)

Reviewed on 10/10/2014

Trade name: 950 PMMA Series Resists in Anisole (Contd. of page 1) H319 Causes serious eye irritation. H335 May cause respiratory irritation. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. No smoking. P210 Do not breathe dust/fume/gas/mist/vapours/spray. P260 Wear protective gloves/protective clothing/eye protection/face protection. P280 Avoid release to the environment. P273 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P301+P310 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for P304+P340 If skin irritation occurs: Get medical advice/attention. P332+P313 If eye irritation persists: Get medical advice/attention. P337+P313 In case of fire: Use for extinction: Alcohol resistant foam. P370+P378 In case of fire: Use for extinction: Fire-extinguishing powder. P370+P378 In case of fire: Use for extinction: Carbon dioxide. P370+P378 IF ON SKIN: Wash with plenty of soap and water. P302+P352 Store in a well-ventilated place. Keep container tightly closed. P403+P233 Dispose of contents/container in accordance with local/regional/national/international P501 regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 1Fire = 2Reactivity = 0· HMIS-ratings (scale 0 - 4) Health = 12 Fire = 2REACTIVITY 0 Reactivity = 0· Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable. 3 Composition/information on ingredients · Chemical characterization: Mixtures Description: Mixture of the substances listed below with nonhazardous additions. Dangerous components: 80-100%

Flam. Liq. 3, H226; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319;

1-20%



Printing date 10/10/2014

Reviewed on 10/10/2014

Trade name: 950 PMMA Series Resists in Anisole

(Contd. of page 2)

#### 4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Inhalation is not an expected route of exposure. If respiratory irritation or distress occurs remove victim to fresh air. Seek medical attention if respiratory irritation or distress continues.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

· For safety reasons unsuitable extinguishing agents:

Water with full jet

Water

· Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

- · Advice for firefighters
- · Protective equipment: Wear SCBA.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- USA



Printing date 10/10/2014

Reviewed on 10/10/2014

Trade name: 950 PMMA Series Resists in Anisole

(Contd. of page 3)

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Use only under yellow light

Keep receptacles tightly sealed.

Use only in well ventilated areas.

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Use explosion-proof apparatus / fittings and spark-proof tools.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers:

Store in inert atmosphere or keep well sealed to prevent the formation of peroxides and other oxidation products.

- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Protect from exposure to the light.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Keep container tightly sealed.

· Specific end use(s) Preparation of radiation sensitive layers in fabrication of microelectronic devices

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory equipment:

In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Contact golve manufacturerer for break-through time.

(Contd. on page 5)



Printing date 10/10/2014

Reviewed on 10/10/2014

Trade name: 950 PMMA Series Resists in Anisole

(Contd. of page 4)

Material of gloves

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

- · Penetration time of glove material Contact glove manufacture for break-through time.
- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR
- · Eye protection:



Tightly sealed goggles

· Body protection: Impervious protective clothing

| Color: Cle Odor: Str. Odour threshold: Not  pH-value: Not  Change in condition  Melting point/Melting range: Una Boiling point/Boiling range: 184  Flash point: 43  Flammability (solid, gaseous): Not  Ignition temperature: 473  Decomposition temperature: Not  Auto igniting: Pro-   | quid ear to light yellow rong at determined.  A °C (363 °F)  °C (109 °F)  At applicable.  5 °C (887 °F)  At determined.  |
|--|--|
| Change in condition Melting point/Melting range: Boiling point/Boiling range:  Flash point:  Flammability (solid, gaseous):  Ignition temperature:  Decomposition temperature:  Auto igniting:  Property of explosion:  Property of the point o | adetermined. 4°C (363°F) °C (109°F) ot applicable. 5°C (887°F) ot determined. oduct is not selfigniting.   |
| Boiling point/Boiling range: 184 Flash point: 43 Flammability (solid, gaseous): Note   Ignition temperature: 475 Decomposition temperature: Note   Auto igniting: Pro-   | 4°C (363°F) °C (109°F) nt applicable. 5°C (887°F) nt determined. oduct is not selfigniting.  |
| Flammability (solid, gaseous): Ignition temperature: Decomposition temperature: Note Auto igniting: Property of explosion: Property of explosion:  | of applicable.  5 °C (887 °F)  of determined.  oduct is not selfigniting.  |
| Decomposition temperature: 473 Decomposition temperature: Note Auto igniting: Pro-   | 5 °C (887 °F)  It determined.  oduct is not selfigniting.  |
| Decomposition temperature: Note Auto igniting: Pro-  | ot determined.  oduct is not selfigniting.   |
| Auto igniting: Pro Danger of explosion: Pro  | oduct is not selfigniting.   |
| Danger of explosion: Pro   | And the second s |
|  | 79 17 17 17 17 17 17 17 17 17 17 17 17 17  |
| mix  | oduct is not explosive. However, formation of explosive air/v<br>xtures are possible.  |
|  | nt determined.<br>ot determined.   |
| Vapor pressure at 20 °C (68 °F): 0.4   | t hPa  |
| Relative density No.   | e Table 1 Other Information below<br>of determined.<br>of determined.<br>of determined.  |
| Solubility in / Miscibility with Water: Wa   | ater miscible No   |

(Contd. on page 7)



# Safety Data Sheet acc. to OSHA HCS

Printing date 10/10/2014

Reviewed on 10/10/2014

|                   | (Contd. of pa                                  |
|-------------------|--|
| Viscosity:        |  |
| Dynamic:          | Not determined.                                |
| Kinematic:        | Not determined.                                |
| Solvent content:  |  |
| VOC content:      | See Table 1 below                              |
| Other information | Table 1. Product specfic gravity and VOC data. |
|                   | Now And Co. Comp. Vol. (c/L)                   |
|                   | Name Number Sp.Grav. Vol. (%by wt.) VOC (g/L)  |
|                   | 950A1 M230001 0.994 99 985                     |
|                   | 950A2 M230002 0.996 98 975                     |
|                   | 950A3 M230003 0.998 97 970                     |
|                   | 950A4 M230004 1.000 96 960                     |
|                   | 950A4.5 M230504 1.001 95.5 958                 |
|                   | 950A5 M230005 1.004 95 955                     |
|                   | 950A5.5 M230505 1.004 94.5 950                 |
|                   | 950A6 M230006 1.005 94 945                     |
|                   | 950A7 M230007 1.007 93 935                     |
|                   | 950A8 M230008 1.009 92 930                     |
|                   | 950A9 M230009 1.010 91 920                     |
|                   | 950A10 M230010 1.012 90 910                    |
|                   | 950A11 M230011 1.014 89 900                    |
|                   | 950A12 M230012 1.016 88 895                    |
|                   | 950A13 M230013 1.018 87 885                    |
|                   | 950A15 M230015 1.022 85 870                    |

### 10 Stability and reactivity

- Reactivity
- · Chemical stability Stable under normal use conditions
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications,
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Phenol

methyl methacrylate

| Informa<br>Acute to |         | n toxicological effects                  |  |
|---------------------|---------|--|--|
| LD/LC5              | 0 valu  | es that are relevant for classification: |  |
| 100-66-             | 3 Anise | ole                                      |  |
|                     |         | 3700 mg/kg (Rat)<br>>5000 mg/kg (rabbit) |  |



Printing date 10/10/2014

Reviewed on 10/10/2014

Trade name: 950 PMMA Series Resists in Anisole

(Contd. of page 6)

Sensitization: No sensitizing effects known.
Experience with humans: No further relevant information available.
Additional toxicological information:
The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

Carcinogenic categories

IARC (International Agency for Research on Cancer)

9011-14-7 Poly(methyl methacrylate)

NTP (National Toxicology Program)

None of the ingredients are listed.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity:

#### 100-66-3 Anisole

EC50/24 h 40 mg/l (daphnia magna)

EC50/96 hr 162 mg/l (green algae)

LC50/48 hr | 120 mg/L (Cyprinus carpio (common carp))

- · Persistence and degradability Moderately /partly biodegradable
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Disposal must be made in accordance with Federal, State, and Local regulations.

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

| 14 Transport information              |        |                 |
|---------------------------------------|--------|-----------------|
| · UN-Number<br>· DOT, ADR, IMDG, IATA | UN1866 |                 |
|                                       |        | (Contd. on page |



Printing date 10/10/2014

Reviewed on 10/10/2014

Trade name: 950 PMMA Series Resists in Anisole (Contd. of page 7) · UN proper shipping name Resin solution, mixture · DOT, ADR RESIN SOLUTION, mixture · IMDG, IATA · Transport hazard class(es) DOT 3 Flammable liquids. · Class · Label · ADR, IMDG, IATA 3 Flammable liquids · Class 3 · Label · Packing group III DOT, ADR, IMDG, IATA · Environmental hazards: No · Marine pollutant: Warning: Flammable liquids · Special precautions for user · Danger code (Kemler): F-E,S-D · EMS Number: · Transport in bulk according to Annex II of Not applicable. MARPOL73/78 and the IBC Code UN1866, Resin solution, mixture, 3, III · UN "Model Regulation":

| · Safety,<br>· Sara | health and environmental regulations/legislation specific for the substance or mix | xture           |
|---------------------|--|-----------------|
| ·Section            | 355 (extremely hazardous substances):  |                 |
| None of             | f the ingredients are listed.  |                 |
| Section             | 313 (Specific toxic chemical listings):  |                 |
| None of             | f the ingredients is listed.   |                 |
| · TSCA (            | Toxic Substances Control Act):   |                 |
| All ingr            | edients are listed or comply with TSCA regulations.                                |                 |
| Proposi             | ition 65   |                 |
| · Chemic            | cals known to cause cancer:  |                 |
| None of             | f the ingredients are listed.  |                 |
|                     |  | (Contd. on page |



Printing date 10/10/2014

Reviewed on 10/10/2014

Trade name: 950 PMMA Series Resists in Anisole (Contd. of page 8) Chemicals known to cause reproductive toxicity for females: None of the ingredients are listed. · Chemicals known to cause reproductive toxicity for males: None of the ingredients are listed. · Chemicals known to cause developmental toxicity: None of the ingredients are listed. · Carcinogenic categories · EPA (Environmental Protection Agency) None of the ingredients are listed. · TLV (Threshold Limit Value established by ACGIH) None of the ingredients are listed. · NIOSH-Ca (National Institute for Occupational Safety and Health) None of the ingredients are listed. · OSHA-Ca (Occupational Safety & Health Administration) None of the ingredients are listed. · New Jersey State Right To Know List 100-66-3 Anisole

- · California SCAQMD Rule 443.1 VOC's: See Table 1 Section 9
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

Anisole

· Hazard statements

H226 Flammable liquid and vapor.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use for extinction: Alcohol resistant foam.

(Contd. on page 10)

(Contd. of page 9)



### Safety Data Sheet acc. to OSHA HCS

Printing date 10/10/2014

Reviewed on 10/10/2014

Trade name: 950 PMMA Series Resists in Anisole

In case of fire: Use for extinction: Fire-extinguishing powder.

P370+P378 P370+P378 In case of fire: Use for extinction: Carbon dioxide.

P302+P352 IF ON SKIN: Wash with plenty of soap and water. Store in a well-ventilated place. Keep container tightly closed. P403+P233

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Product safety department
- · Contact: Mr. Cole

#### · Revision History:

The business address of the manufacturer in Section 1 was updated. The hazard classification and precautionary statements for the mixture in Section 2 were revised. The toxicology data in Sections 11 and 12 were revised.

- · Date of preparation / last revision 10/10/2014 / 1
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent